

- 32 Canisters, yet same footprint
- 2x Faster, Simple & Reliable
- Easy logistics





The **X-SMART XL** automatic paint dispenser enables you to expand your market and explore new POS channels and opportunities.

X-SMART XL is available upto 32 canisters with your choice of decorative and solvent canister configuration, yet compact in size can fit into any small or mid-level size outlet.

The compact packaging minimizes transport costs and it can be assembled in a matter of minutes. The innovative modular design makes the **X-SMART XL** easy and cost effective to maintain.



X-SMART XL: Simplicity makes sense. Our aim was to provide our customers with a trouble-free solution. Their daily operation is best served with an affordable and reliable dispenser: compact, low maintenance and user-friendly.

The **X-SMART XL** dispenser can be customized with 360° advertising possibilities for maximum exposure.

Specifications & Technical Data

General

- Automatic sequential
- Water based, universal
- Solvent based (optional)
- Bi-directional Turntable

Canisters

- Upto 32 canisters
- Material: POM; PP
- Size: 16 x 2.3 Lt + 16 x 1.3 L
- Click-on-click-off
- Patented optimal stirrer design

Pump

- Piston pump
- Size: 43 ml
- Flow rate: 0.5 Lt/min
- Min. dispense: 0.077 ml (1/384 fl.oz.)
- Nozzle diameter: 4 mm
- Polymeric needle valve
- Seals material: Viton, Viton Extreme
- Calibration: 1st machine only.
- Subsequent machines copied calibration files. Calibration lasts machine lifetime

Nozzles

- Air tight integrated nozzle closures
- Nozzle cleaning system: passive brush

Can table

- Manual can shelf
- Dimensions: 38 x 31 cm (W x D)
- Can loading height: 26 cm
- Max. can height: 48 cm
- Optical can sensor

Dimension & weight

- HWD 131 x 83 x 83 cm (with top cover)
- Filling height: 120 cm
- Packaging HWD 115 x 90 x 90 cm
- Net weight: 70 kg

Software

- PrismaPro easy to use
- Local language compatible
- Prisma-RT mobile app compatible

Maintenance & Operations

- Low level (only purge & brush clean)
- Low TCO
- Ease of use
- Minimal operator training
- Visual LED error indicator

Power supply & safety

■ 110V/230V +/- 10%, 50Hz/60Hz









For further enquiries, please contact

FAST & FLUID MANAGEMENT

India: S14, Solitaire Corporate Park, 1st Floor, Chakala, Andheri E, Mumbai 400093

Tel: +91 22 6643 5500 Email: info.fmt@idexcorp.com **SE Asia**: 18 Boon Lay Way #09-97/98, Tradehub 21, Singapore 609966

Tel +65 6684 7318 Email: FAU-Sales@idexcorp.com

Oceania: 10 Resolution Drive, Unanderra NSW 2526, Australia Tel +61 2 4271 7111 Email: FAU-Sales@idexcorp.com

